

Configure Elasticsearch/Kibana for TLS and Authentication

1. Shutdown elk-cluster
2. Add certificate path to elasticsearch config in docker-compose.yml

```
volumes:  
  - ./certs:/certs
```

3. Start elasticsearch

```
$ docker-compose up -d elasticsearch
```

4. Create certificates

```
$ docker exec -it elk-test-elasticsearch bash
```

```
[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil  
ca -pem -ca-dn "cn=Elastic Stack CA"
```

This tool assists you in the generation of X.509 certificates and certificate

signing requests for use with SSL/TLS in the Elastic stack.

```
[ ... ]
```

If you elect to generate PEM format certificates (the -pem option), then the output will be a zip file containing individual files for the CA certificate and private key

Please enter the desired output file [elastic-stack-ca.zip]:

```
[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/ elastic-stack-ca.zip
```

```
[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil  
http
```

```
## Elasticsearch HTTP Certificate Utility
```

```
[ ... ]
```

```
## Do you wish to generate a Certificate Signing Request (CSR)?
```

```
[ ... ]
```

```
Generate a CSR? [y/N]n
```

```
## Do you have an existing Certificate Authority (CA) key-pair that you  
wish to use to sign your certificate?
```

[...]

Use an existing CA? [y/N]y

What is the path to your CA?

CA Path: /certs/ca/ca.crt

What is the path to your CA key?

/certs/ca/ca.crt appears to be a PEM formatted certificate file.
In order to use it for signing we also need access to the private key
that corresponds to that certificate.

CA Key: /certs/ca/ca.key

For how long should your certificate be valid? [5y]

[...]

Generate a certificate per node? [y/N]y

What is the name of node #1?

This name will be used as part of the certificate file name, and as a
descriptive name within the certificate.

You can use any descriptive name that you like, but we recommend using
the name
of the Elasticsearch node.

node #1 name: elk-test-elasticsearch

Which hostnames will be used to connect to elk-test-elasticsearch?

[...]

Enter all the hostnames that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.

elk-test-elasticsearch

You entered the following hostnames.

- elk-test-elasticsearch

Is this correct [Y/n]y

Which IP addresses will be used to connect to elk-test-
elasticsearch?

Enter all the IP addresses that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.

[...]

You did not enter any IP addresses.

Is this correct [Y/n]y

Other certificate options

The generated certificate will have the following additional configuration values. These values have been selected based on a combination of the information you have provided above and secure defaults. You should not need to change these values unless you have specific requirements.

Key Name: elk-test-elasticsearch
Subject DN: CN=elk-test-elasticsearch
Key Size: 2048

Do you wish to change any of these options? [y/N]n
Generate additional certificates? [Y/n]n

What password do you want for your private key(s)?

Your private key(s) will be stored in a PKCS#12 keystore file named "http.p12".
This type of keystore is always password protected, but it is possible to use a blank password.

If you wish to use a blank password, simply press <enter> at the prompt below.
Provide a password for the "http.p12" file: [<ENTER> for none]

Where should we save the generated files?

A number of files will be generated including your private key(s), public certificate(s), and sample configuration options for Elastic Stack products.

These files will be included in a single zip archive.

What filename should be used for the output zip file?
[/usr/share/elasticsearch/elasticsearch-ssl-http.zip]

Zip file written to /usr/share/elasticsearch/elasticsearch-ssl-http.zip

[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/

```
elasticsearch-ssl-http.zip
Archive:  elasticsearch-ssl-http.zip
  creating: /certs/elasticsearch/
  inflating: /certs/elasticsearch/README.txt
  inflating: /certs/elasticsearch/http.p12
  inflating: /certs/elasticsearch/sample-elasticsearch.yml
  creating: /certs/kibana/
  inflating: /certs/kibana/README.txt
  inflating: /certs/kibana/elasticsearch-ca.pem
  inflating: /certs/kibana/sample-kibana.yml
```

5. Configure elasticsearch for TLS & X-Pack Security

1. Shutdown elasticsearch

```
$ docker-compose down
Stopping elk-test-elasticsearch ... done
Removing elk-test-elasticsearch ... done
Removing network elk-test_default
```

2. Add certificate mount to docker-compose

```
volumes:
  -
    ./elasticsearch/config/elasticsearch.p12:/usr/share/elasticsearch/
    config/elasticsearch.p12:ro
```

3. Copy P12 file to correct place

```
cp certs/elasticsearch/http.p12
elasticsearch/config/elasticsearch.p12
```

4. Update elasticsearch.yml

```
# grep xpack elasticsearch/config/elasticsearch.yml
xpack.security.enabled: true
xpack.security.http.ssl.enabled: true
xpack.security.http.ssl.verification_mode: "certificate"
xpack.security.http.ssl.keystore.path: "elasticsearch.p12"
```

[kb](#), [elasticsearch](#)

From:

<http://fortytwo.adurias.org/> - **Fortytwo - Answer to the Ultimate Question of Life, the Universe, and Everything**

Permanent link:

<http://fortytwo.adurias.org/elasticsearch-tls?rev=1604747024>

Last update: **2020/11/07 12:03**

