

Configure Elasticsearch/Kibana for TLS and Authentication

Create Certificates

1. Shutdown elk-cluster
2. Add certificate path to elasticsearch config in docker-compose.yml

```
volumes:  
  - ./certs:/certs
```

3. Start elasticsearch

```
$ docker-compose up -d elasticsearch
```

4. Create certificates

```
$ docker exec -it elk-test-elasticsearch bash  
  
[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil  
ca -pem -ca-dn "cn=Elastic Stack CA"  
This tool assists you in the generation of X.509 certificates and  
certificate  
signing requests for use with SSL/TLS in the Elastic stack.  
  
[ ... ]  
  
If you elect to generate PEM format certificates (the -pem option),  
then the output will  
be a zip file containing individual files for the CA certificate and  
private key  
  
Please enter the desired output file [elastic-stack-ca.zip]:  
[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/ elastic-  
stack-ca.zip  
  
[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil  
http  
  
## Elasticsearch HTTP Certificate Utility  
  
[ ... ]  
  
## Do you wish to generate a Certificate Signing Request (CSR)?  
  
[ ... ]  
  
Generate a CSR? [y/N]n
```

```
## Do you have an existing Certificate Authority (CA) key-pair that you
wish to use to sign your certificate?

[ ... ]

Use an existing CA? [y/N]y

## What is the path to your CA?

CA Path: /certs/ca/ca.crt

## What is the path to your CA key?

/certs/ca/ca.crt appears to be a PEM formatted certificate file.
In order to use it for signing we also need access to the private key
that corresponds to that certificate.

CA Key: /certs/ca/ca.key

For how long should your certificate be valid? [5y]

[ ... ]

Generate a certificate per node? [y/N]y

## What is the name of node #1?

This name will be used as part of the certificate file name, and as a
descriptive name within the certificate.

You can use any descriptive name that you like, but we recommend using
the name
of the Elasticsearch node.

node #1 name: elk-test-elasticsearch

## Which hostnames will be used to connect to elk-test-elasticsearch?

[ ... ]

Enter all the hostnames that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.

elk-test-elasticsearch

You entered the following hostnames.

- elk-test-elasticsearch

Is this correct [Y/n]y
```

```
## Which IP addresses will be used to connect to elk-test-elasticsearch?
```

```
Enter all the IP addresses that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.
```

```
[ ... ]
```

```
You did not enter any IP addresses.
```

```
Is this correct [Y/n]y
```

```
## Other certificate options
```

```
The generated certificate will have the following additional
configuration
values. These values have been selected based on a combination of the
information you have provided above and secure defaults. You should not
need to
change these values unless you have specific requirements.
```

```
Key Name: elk-test-elasticsearch
Subject DN: CN=elk-test-elasticsearch
Key Size: 2048
```

```
Do you wish to change any of these options? [y/N]n
Generate additional certificates? [Y/n]n
```

```
## What password do you want for your private key(s)?
```

```
Your private key(s) will be stored in a PKCS#12 keystore file named
"http.p12".
This type of keystore is always password protected, but it is possible
to use a
blank password.
```

```
If you wish to use a blank password, simply press <enter> at the prompt
below.
```

```
Provide a password for the "http.p12" file: [<ENTER> for none]
```

```
## Where should we save the generated files?
```

```
A number of files will be generated including your private key(s),
public certificate(s), and sample configuration options for Elastic
Stack products.
```

```
These files will be included in a single zip archive.
```

```
What filename should be used for the output zip file?
[/usr/share/elasticsearch/elasticsearch-ssl-http.zip]
```

```
Zip file written to /usr/share/elasticsearch/elasticsearch-ssl-http.zip

[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/
elasticsearch-ssl-http.zip
Archive:  elasticsearch-ssl-http.zip
  creating: /certs/elasticsearch/
  inflating: /certs/elasticsearch/README.txt
  inflating: /certs/elasticsearch/http.p12
  inflating: /certs/elasticsearch/sample-elasticsearch.yml
  creating: /certs/kibana/
  inflating: /certs/kibana/README.txt
  inflating: /certs/kibana/elasticsearch-ca.pem
  inflating: /certs/kibana/sample-kibana.yml
```

Configure elasticsearch for TLS & X-Pack Security

1. Shutdown elasticsearch

```
$ docker-compose down
Stopping elk-test-elasticsearch ... done
Removing elk-test-elasticsearch ... done
Removing network elk-test_default
```

2. Add certificate mount to docker-compose

```
volumes:
  -
  ./elasticsearch/config/elasticsearch.p12:/usr/share/elasticsearch/confi
g/elasticsearch.p12:ro
```

3. Copy P12 file to correct place

```
cp certs/elasticsearch/http.p12 elasticsearch/config/elasticsearch.p12
```

4. Update elasticsearch.yml

```
$ grep xpack elasticsearch/config/elasticsearch.yml
xpack.security.enabled: true
xpack.security.http.ssl.enabled: true
xpack.security.http.ssl.verification_mode: "certificate"
xpack.security.http.ssl.keystore.path: "elasticsearch.p12"
```

5. Start elasticsearch

6. Create Users

[kb, elasticsearch](#)

From:

<http://fortytwo.adurias.org/> - **Fortytwo - Answer to the Ultimate Question of Life, the Universe, and Everything**

Permanent link:

<http://fortytwo.adurias.org/elasticsearch-tls?rev=1604747167>

Last update: **2020/11/07 12:06**

