

Configure Elasticsearch/Kibana for TLS and Authentication

Create Certificates

1. Shutdown elk-cluster
2. Add certificate path to elasticsearch config in docker-compose.yml

```
services:
  elasticsearch:
    volumes:
      - ./certs:/certs
```

3. Start elasticsearch

```
$ docker-compose up -d elasticsearch
```

4. Create certificates

```
$ docker exec -it elk-test-elasticsearch bash

[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil
ca -pem -ca-dn "cn=Elastic Stack CA"
This tool assists you in the generation of X.509 certificates and
certificate
signing requests for use with SSL/TLS in the Elastic stack.

[ ... ]

If you elect to generate PEM format certificates (the -pem option),
then the output will
be a zip file containing individual files for the CA certificate and
private key

Please enter the desired output file [elastic-stack-ca.zip]:
[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/ elastic-
stack-ca.zip

[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-certutil
http

## Elasticsearch HTTP Certificate Utility

[ ... ]

## Do you wish to generate a Certificate Signing Request (CSR)?

[ ... ]
```

```
Generate a CSR? [y/N]n

## Do you have an existing Certificate Authority (CA) key-pair that you
wish to use to sign your certificate?

[ ... ]

Use an existing CA? [y/N]y

## What is the path to your CA?

CA Path: /certs/ca/ca.crt

## What is the path to your CA key?

/certs/ca/ca.crt appears to be a PEM formatted certificate file.
In order to use it for signing we also need access to the private key
that corresponds to that certificate.

CA Key: /certs/ca/ca.key

For how long should your certificate be valid? [5y]

[ ... ]

Generate a certificate per node? [y/N]y

## What is the name of node #1?

This name will be used as part of the certificate file name, and as a
descriptive name within the certificate.

You can use any descriptive name that you like, but we recommend using
the name
of the Elasticsearch node.

node #1 name: elk-test-elasticsearch

## Which hostnames will be used to connect to elk-test-elasticsearch?

[ ... ]

Enter all the hostnames that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.

elk-test-elasticsearch

You entered the following hostnames.

- elk-test-elasticsearch
```

```
Is this correct [Y/n]y

## Which IP addresses will be used to connect to elk-test-
elasticsearch?

Enter all the IP addresses that you need, one per line.
When you are done, press <ENTER> once more to move on to the next step.

[ ... ]

You did not enter any IP addresses.

Is this correct [Y/n]y

## Other certificate options

The generated certificate will have the following additional
configuration
values. These values have been selected based on a combination of the
information you have provided above and secure defaults. You should not
need to
change these values unless you have specific requirements.

Key Name: elk-test-elasticsearch
Subject DN: CN=elk-test-elasticsearch
Key Size: 2048

Do you wish to change any of these options? [y/N]n
Generate additional certificates? [Y/n]n

## What password do you want for your private key(s)?

Your private key(s) will be stored in a PKCS#12 keystore file named
"http.p12".
This type of keystore is always password protected, but it is possible
to use a
blank password.

If you wish to use a blank password, simply press <enter> at the prompt
below.
Provide a password for the "http.p12" file: [<ENTER> for none]

## Where should we save the generated files?

A number of files will be generated including your private key(s),
public certificate(s), and sample configuration options for Elastic
Stack products.

These files will be included in a single zip archive.

What filename should be used for the output zip file?
```

```
[/usr/share/elasticsearch/elasticsearch-ssl-http.zip]
```

```
Zip file written to /usr/share/elasticsearch/elasticsearch-ssl-http.zip
```

```
[root@elk-test-elasticsearch elasticsearch]# unzip -d /certs/  
elasticsearch-ssl-http.zip
```

```
Archive:  elasticsearch-ssl-http.zip  
  creating: /certs/elasticsearch/  
  inflating: /certs/elasticsearch/README.txt  
  inflating: /certs/elasticsearch/http.p12  
  inflating: /certs/elasticsearch/sample-elasticsearch.yml  
  creating: /certs/kibana/  
  inflating: /certs/kibana/README.txt  
  inflating: /certs/kibana/elasticsearch-ca.pem  
  inflating: /certs/kibana/sample-kibana.yml
```

Configure elasticsearch for TLS & X-Pack Security

1. Shutdown elasticsearch

```
$ docker-compose down  
Stopping elk-test-elasticsearch ... done  
Removing elk-test-elasticsearch ... done  
Removing network elk-test_default
```

2. Add certificate mount to docker-compose

```
volumes:  
  -  
  ./elasticsearch/config/elasticsearch.p12:/usr/share/elasticsearch/confi  
g/elasticsearch.p12:ro
```

3. Copy P12 file to correct place

```
cp certs/elasticsearch/http.p12 elasticsearch/config/elasticsearch.p12
```

4. Update elasticsearch.yml

```
$ grep xpack elasticsearch/config/elasticsearch.yml  
xpack.security.enabled: true  
xpack.security.http.ssl.enabled: true  
xpack.security.http.ssl.verification_mode: "certificate"  
xpack.security.http.ssl.keystore.path: "elasticsearch.p12"
```

5. Start elasticsearch

```
docker-compose up -d elasticsearch  
Creating network "elk-test_default" with the default driver  
Creating elk-test-elasticsearch ... done
```

6. Create Users

```
$ docker exec -it elk-test-elasticsearch bash
[root@elk-test-elasticsearch elasticsearch]# bin/elasticsearch-setup-
passwords auto
Initiating the setup of passwords for reserved users
elastic,apm_system,kibana,kibana_system,logstash_system,beats_system,remote_monitoring_user.
The passwords will be randomly generated and printed to the console.
Please confirm that you would like to continue [y/N]y

Changed password for user apm_system
PASSWORD apm_system = ***

Changed password for user kibana_system
PASSWORD kibana_system = ***

Changed password for user kibana
PASSWORD kibana = ***

Changed password for user logstash_system
PASSWORD logstash_system = ***

Changed password for user beats_system
PASSWORD beats_system = ***

Changed password for user remote_monitoring_user
PASSWORD remote_monitoring_user = ***

Changed password for user elastic
PASSWORD elastic = ***
```

Configure Kibana for TLS and User Authentication

[kb](#), [elasticsearch](#)

From:

<http://fortytwo.adurias.org/> - **Fortytwo - Answer to the Ultimate Question of Life, the Universe, and Everything**

Permanent link:

<http://fortytwo.adurias.org/elasticsearch-tls?rev=1604747819>

Last update: **2020/11/07 12:16**

