

# Simple IP-Address Watchdog

```
$ crontab -l
@reboot /usr/bin/sleep 60 && /usr/bin/curl -kso /dev/null
https://adurias.org/watchdog?hostname=$(hostname)\&address=$(/usr/sbin/ip -4
route get 1.0.0.0 | /usr/bin/awk '/dev/ { print $7 }')
```

Results are seen in the access.log of the webserver placed in the curl call

```
$ grep watchdog access.log
adurias.org 80.108.189.88 - - [28/May/2022:10:13:53 +0200] "GET
/watchdog?hostname=kali-raspberry-pi HTTP/1.1" 404 434 "-" "curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:14:07 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:14:20 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:14:24 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:14:32 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:21:05 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:30:01 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
adurias.org 80.108.189.88 - - [28/May/2022:10:34:14 +0200] "GET
/watchdog?hostname=kali-raspberry-pi&address=10.42.1.5 HTTP/1.1" 404 434 "-"
"curl/7.83.0"
```

[kb, linux](#)

From:

<http://fortytwo.adurias.org/> - **Fortytwo - Answer to the Ultimate Question of Life, the Universe, and Everything**

Permanent link:

<http://fortytwo.adurias.org/ip-address-watchdog?rev=1653727164>

Last update: **2022/05/28 10:39**

