

MySQL useful commands

User & Permissions

Create Database User

```
CREATE USER 'username'@'localhost' IDENTIFIED BY 'password';
```

Grant Permissions

```
GRANT ALL privileges ON dbname.* TO 'username'@'localhost'; FLUSH privileges;
```

Set new DB user password

```
SET PASSWORD FOR 'user-name-here'@'hostname-name-here' = PASSWORD('new-password-here');
```

Delete Database User

Update field and replace string

```
UPDATE TABLE SET FIELD = REPLACE(FIELD, 'old string', 'new string')
```

Restore MySQL system database in docker environment

```
$ docker run --detach --rm --name mariadb-restore \  
  --env MARIADB_USER=user \  
  --env MARIADB_PASSWORD=password \  
  --env MARIADB_ROOT_PASSWORD=root \  
  --volume /srv/base-mariadb/BACKUP:/BACKUP:ro \  
  --volume $PWD/data:/var/lib/mysql \  
  mariadb:10.5
```

```
$ docker exec -it mariadb-restore bash  
# mysql -u root -p mysql < /BACKUP/mysql.dump  
# echo "flush privileges" | mysql -u root -p
```

[kb, mysql](#)

From:

<http://fortytwo.adurias.org/> - **Fortytwo - Answer to the Ultimate Question of Life, the Universe, and Everything**

Permanent link:

<http://fortytwo.adurias.org/mysql-useful-commands?rev=1725639617>

Last update: **2024/09/06 18:20**

